

WALLBOX DC 30

WALLBOX DC 30

up to **30 kW**
30 min
to 100 KM route



up to **30 kW**

WALLBOX DC

30

STANDARD

30

[kW]

CONNECTORS	CCS (4 m)	●
HOUSING	RAL Colour 9016	●
USER INTERFACE	7"Touchscreen display with integrated RFID card reader	●
METERS	Output energy meter	●
COMMUNICATION	GSM (LTE) Ekoenergetyka	●
	GSM (LTE) Client	●
	Ethernet	●
Order code:		WAL-A210B0000H-9016

EXTRA PAID OPTIONS

CONNECTORS	CCS (4 m) / CCS (4m)	○
	CCS (4 m) / CHAdeMO (4m)	○
HOUSING	RAL Colour (Other)	○
	Additional branding	○
	Anti-graffiti	○

● standard / available ○ option (extra paid) ✖ unavailable - absent

WALLBOX DC

30

TECHNICAL SPECIFICATIONS

30

[kW]

INPUT	Power supply [V/Hz]	AC, 3 x 400 / 50
	Connection power [kVA]	33
	Connection to mains	Cable connection
	Power factor	>0,98 (for power output > 25%)
OUTPUT	Eiciency [%]	> 94
	Maximum charging current [A]	100
	Output voltage range [V]	150 - 1000
COMMUNICATION	Charging mode	IEC 61851-1, IEC 61851-23, IEC 61851-24, ISO 15118, DIN 70121, CHAdeMO rev. 1.2
	Protocol	OCPP 1.6-J OCPP 2.0.1
GENERAL	Housing	Aluminium
	Protection rating (excluding HMI)	IP54 / IK10
	Overall dimensions [mm] [H x W x D]	1600 x 900 x 200
	Weight [kg]	< 65
	Noise [dBA]	< 55
	Operating temperature range [°C]	-25 - +55 > 40 possible output power limitation
	Operating altitude [m]	≤ 2000
	Compliance with standards	CE, LVD 2014/35/UE, EMC 2014/30UE, RED 2014/53/UE

Preliminary technical data